Article Print o Versio	date (	111XXX003 )7.06.2020 I.0	UNDERPAINTING 0 Revision date 07.07 Issue date 07.07.20	.2016	Pag	EN ge 1 / 7
	<b>SECTION 1</b>	: Identification	of the substance/n	nixture and of	f the company	//undertaking
1.1.	product iden	tifiers				
	•	anufacturer/sup of the substance		111XXX003 UNDERPAINT MIXING 007	NG 003	
1.2.	Relevant ide	ntified uses of t	he substance or mixt	ure and uses a	dvised against	
	Artists supply	ntified uses: and hobby prep paints, thinners,				
1.3.	Details of the	e supplier of the	safety data sheet			
	Supplier (ma Canson Austr 6/26-30 Foun Seven Hills N	alia dry Road	orter/downstream use	Telephone: 028	38255300 ephone: 131126	
	Dept. respor	sible for inform	ation:			
	E-mail			sales.au@cans	son.com	
1.4.						
	SECTION 2	: Hazards iden	tification			
2.1.	Classificatio The mixture is Aquatic Chron Classificatio	s classified as ha nic 3 / H412 <b>n according to</b>	Regulation (EC) No 12 azardous according to r Hazardous to the aqu Directive 67/548/EEC ot hazardous according	regulation (EC) uatic environme or 1999/45/EC	No 1272/2008 [C nt Harmfu	CLP]. Il to aquatic life with long lasting effects.
2.2.	Label eleme					
	-		abelled according to E		corresponding na	ational laws.
			Ilation (EC) No. 1272/	2008 [CLP]		
	Hazard picto	grams				
	Hazard state H412 Precautional		I to aquatic life with lon	ng lasting effects	5.	
	P101 P102 P103 P273	If medie Keep o Read la Avoid r	cal advice is needed, h ut of the reach of childr abel before use. elease to the environm	ent.		
	P501	Dispos	e of contents/container	in accordance	with local legisla	tion.
	contains:	not app	licable			
	Supplement	al Hazard inform not app	nation (EU)			
	Labelling (67	7/548/EEC or 19				
	Hazard state		<i>I</i>			
	Precautional	ry statements				
	contains:					

Special provisions concerning the labelling of certain mixtures

Article No.:	111XXX003	UNDERPAINTING 003		
Print date	07.06.2020	Revision date 07.07.2016	EN	
Version	1.0	Issue date 07.07.2016	Page 2 / 7	

#### 2.3. Other hazards

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

Mixtures		
Product descript	tion / chemical characterization	
Description	oil paint	
Hazardous ingre	dients	
Classification ac	cording to Regulation (EC) No 1272/2008 [CLP]	
EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification:	Remark
215-222-5		
1314-13-2	zinc oxide	1 - 2,5
030-013-00-7	Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	·
Classification ac	cording to Directive 67/548/EEC or 1999/45/EC	
EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification:	Remark

## Additional information

Full text of R-phrases: see section 16. Full text of classification: see section 16

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Extinguishing media which must not be used for safety reasons:

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Article No.:	111XXX003	UNDERPAINTING 003		
Print date	07.06.2020	Revision date 07.07.2016	EN	
Version	1.0	Issue date 07.07.2016	Page 3 / 7	

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

## SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

# 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limit values:

zinc oxide INDEX No. 030-013-00-7 / EC No. 215-222-5 / CAS No. 1314-13-2 TWA: 5 mg/m3 STEL: 10 mg/m3

## Additional information

Article No.:	111XXX003	UNDERPAINTING 003	
Print date	07.06.2020	Revision date 07.07.2016	EN
Version	1.0	Issue date 07.07.2016	Page 4 / 7

TWA : long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Occupational exposure controls

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye protection

Wear closely fitting protective glasses in case of splashes.

### **Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

	Appearance:	Liquid					
	Physical state	Liquid					
	Colour	refer to label					
	Odour	characteristic					
	Safety relevant basis data		Unit	Method	Remark		
	Flash point:	> 99	°C	DIN 53213			
	Ignition temperature in °C:	not applicable	°C				
	Lower explosion limit	not applicable	Vol-%				
	Upper explosion limit	not applicable	Vol-%				
	Vapour pressure at 20 °C::	not applicable	mbar				
	Density at 20 °C::	1,00	g/cm³				
	Water solubility (g/L)	insoluble					
	pH at 20 °C::	-					
	Viscosity at 20 °C:	> 50	mPa*s				
	Solvent separation test (%)	< 3	%				
	boiling point in °C at 101,3 kPa	185	°C				
9.2.	Other information:						

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. Vapours form explosive mixtures with air.

Article No.:	111XXX003	UNDERPAINTING 003		
Print date	07.06.2020	Revision date 07.07.2016	EN	
Version	1.0	Issue date 07.07.2016	Page 5 / 7	

#### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

## 10.5. Incompatible materials

# 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

### **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

#### 11.1. Information on toxicological effects

### Acute toxicity

Toxicological data are not available.

### skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

#### Respiratory or skin sensitisation

Toxicological data are not available.

#### Specific target organ toxicity

Toxicological data are not available.

#### Aspiration hazard

Toxicological data are not available.

#### Practical experience/human evidence

#### Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

There is no information available on the preparation itself .

#### **SECTION 12: Ecological information**

#### overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Toxicological data are not available.

#### Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

# 12.2. Persistence and degradability

Toxicological data are not available.

# 12.3. Bioaccumulative potential

Toxicological data are not available.

# 12.4. Mobility in soil

Toxicological data are not available.

## 12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

Article No.:	111XXX003	UNDERPAINTING 003		
Print date	07.06.2020	Revision date 07.07.2016	EN	
Version	1.0	Issue date 07.07.2016	Page 6 / 7	

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

### Appropriate disposal / Product

# Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

### List of proposed waste codes/waste designations in accordance with EWC

waste paint and varnish containing organic solvents or other dangerous substances

# packaging

080111\*

# Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

	<b>SECTION 14: Transport information</b>	I
	No dangerous good in sense of this tra	insport regulation.
14.1.	UN number	
		not applicable
14.2.	UN proper shipping name	
14.3.	Transport hazard class(es)	
		not applicable
14.4.	Packing group	
		not applicable
14.5.	Environmental hazards	
	Land transport (ADR/RID)	not applicable
	Marine pollutant	not applicable
14.6.	Special precautions for user	
	Transport always in closed, upright and sa case of an accident or leakage. Advices on safe handling: see parts 6 - 8	afe containers. Make sure that persons transporting the product know what to do in
	Further information	
	Land transport (ADR/RID)	
	tunnel restriction code	<u> </u>
	Sea transport (IMDG)	
	EmS-No.	not applicable
14.7.	Transport in bulk according to Annex I	l of Marpol and the IBC Code
	not applicable	
	SECTION 15: Regulatory information	n
15.1.	Safety, health and environmental regula	ations/legislation specific for the substance or mixture
	EU legislation	•
	•	pout limitation of emissions of volatile organic compounds (VOC-guideline).

 Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

 VOC-value (in g/L) ISO 11890-2:
 0

 VOC-value (in g/L) ASTM D 2369:
 0

## National regulations

# **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

# Other regulations, restrictions and prohibition regulations

Article No.:	111XXX003	UNDERPAINTING 003		
Print date	07.06.2020	Revision date 07.07.2016	EN	
Version	1.0	Issue date 07.07.2016	Page 7 / 7	

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

# 16. Other information

# Full text of classification in section 3:

Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting
		effects.

### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.