## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 114XXX008 PAPER VARNISH

 Print date
 08.06.2020
 Revision date 20.09.2016
 EN

 Version
 1.0
 Issue date 20.09.2016
 Page 1 / 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. product identifiers

Article No. (manufacturer/supplier): 114XXX008
Identification of the substance or mixture PAPER VARNISH

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

## Supplier (manufacturer/importer/downstream user/distributor):

Canson Australia

6/26-30 Foundry Road Telephone: 0288255300 Seven Hills NSW 2147 Emergency telephone: 131126

Dept. responsible for information:

E-mail sales.au@canson.com

1.4.

2.1.

## **SECTION 2: Hazards identification**

## Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skin.

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skir Acute Tox. 4 / H332 Acute toxicity (inhalative) Harmful if inhaled.

Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Eye Irrit. 2 / H319 Serious eye damage/eye irritation

Skin Sens. 1 / H317 Respiratory or skin sensitisation

Skin Irrit. 2 / H315 Causes skin irritation.

Causes skin irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

## **Hazard pictograms**







## Warning

## **Hazard statements**

H226 Flammable liquid and vapour.

H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of the reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P243 Take precautionary measures against static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article No.: 114XXX008 PAPER VARNISH Print date 08.06.2020 Revision date 20.09.2016

Revision date 20.09.2016 EN Issue date 20.09.2016 Page 2 / 8

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use foam to extinguish.
P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local legislation.

contains:

Version

Methanol turpentine, oil

Supplemental Hazard information (EU)

not applicable

#### 2.3. Other hazards

## **SECTION 3: Composition / information on ingredients**

#### 3.2. Mixtures

Product description / chemical characterization

**Description** Alkydharz-Lack

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

CAS No.	Chemical name	Wt %	
INDEX No.	classification:	Remark	
232-350-7			
8006-64-2	turpentine, oil	50 - 100	
650-002-00-6	Flam. Liq. 3 H226 / Acute Tox. 4 H332 / Acute Tox. 4 H312 / Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411		
200-659-6			
67-56-1	Methanol	< 0,5	
603-001-00-X	Flam. Liq. 2 H225 / Acute Tox. 3 H331 / Acute Tox. 3 H311 / Acute Tox. 3 H301 / STOT SE 1 H370		

#### **Additional information**

Full text of classification: see section 16

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

## In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

## Following skin contact

Take off immediately all contaminated clothing. After contact with molten product, cool skin area rapidly with cold water. Allow stiffening. Take up mechanically. When in doubt or if symptoms are observed, get medical advice.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). When in doubt or if symptoms are observed, get medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

PAPER VARNISH 114XXX008 Article No.: 08.06.2020

Revision date 20.09.2016 Print date ΕN Issue date 20.09.2016 Page 3 / 8 Version

#### 4.3. Indication of any immediate medical attention and special treatment needed

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Extinguishing media which must not be used for safety reasons:

strong water jet

## 5.2. Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### Special protective equipment for firefighters

Provide a conveniently located respiratory protective device.

#### Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

#### **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

## Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Clean using cleansing agents. Do not use solvents.

### Reference to other sections

Observe protective provisions (see section 7 and 8).

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advices on safe handling

Follow the legal protection and safety regulations.

#### Precautions against fire and explosion:

Usual measures for fire prevention.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed.

## Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

## Occupational exposure limit values:

turpentine, oil

INDEX No. 650-002-00-6 / EC No. 232-350-7 / CAS No. 8006-64-2

TWA: 566 mg/m3; 100 ppm STEL: 850 mg/m3; 150 ppm

Methanol

INDEX No. 603-001-00-X / EC No. 200-659-6 / CAS No. 67-56-1

TWA: 266 mg/m3; 200 ppm STEL: 333 mg/m3; 250 ppm

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 114XXX008 PAPER VARNISH
Print date 08.06.2020 Revision date 20.09.2016
Version 1.0 Issue date 20.09.2016

**Additional information** 

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

**DNEL:** 

Methanol

INDEX No. 603-001-00-X / EC No. 200-659-6 / CAS No. 67-56-1 DNEL acute dermal, short-term (local), Workers: 40 mg/kg DNEL long-term dermal (systemic), Workers: 40 mg/kg DNEL acute inhalative (local), Workers: 260 mg/m³ DNEL acute inhalative (systemic), Workers: 200 mg/m³ DNEL long-term inhalative (local), Workers: 260 mg/m³ DNEL long-term inhalative (systemic), Workers: 260 mg/m³

DNEL short-term oral (acute), Consumer: 8 mg/kg DNEL long-term oral (repeated), Consumer: 8 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 8 mg/kg

DNEL long-term dermal (systemic), Consumer: 8 mg/kg DNEL acute inhalative (local), Consumer: 50 mg/m³ DNEL acute inhalative (systemic), Consumer: 50 mg/m³ DNEL long-term inhalative (local), Consumer: 50 mg/m³ DNEL long-term inhalative (systemic), Consumer: 50 mg/m³

PNEC:

Methanol

INDEX No. 603-001-00-X / EC No. 200-659-6 / CAS No. 67-56-1

PNEC aquatic, freshwater: 154 mg/l PNEC aquatic, marine water: 15.4 mg/l PNEC sediment, freshwater: 570.4 mg/kg

PNEC, soil: 23.5 mg/kg

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

ΕN

Page 4 / 8

## Occupational exposure controls

## Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

## Eye protection

Wear closely fitting protective glasses in case of splashes.

#### Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance:

Physical state Liquid

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: Print date Version 114XXX008 08.06.2020 PAPER VARNISH Revision date 20.09.2016 Issue date 20.09.2016

EN Page 5 / 8

Colourrefer to labelOdourcharacteristic

Safety relevant basis data		Unit	Method	Remark
Flash point (°C)	< 50	°C	DIN 53213	
Ignition temperature in °C:	220	°C		
Lower explosion limit	0,7	Vol-%		
Upper explosion limit	15	Vol-%		
Vapour pressure at 20 °C::	4,52			
Density at 20 °C::	1,00	g/cm³		
Water solubility (g/L)	insoluble			
pH at 20 °C::	-			
Viscosity at 20 °C:	< 100	mPa*s		
Solvent separation test (%)	< 3	%		
Solid content (%):	30,00	Wt %		
	70	Wt %		
	0	Wt %		

#### 9.2. Other information:

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

## 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7

## 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

## 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke. Decompostion takes place from temperatures above: at 160 °C:

## **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

#### 11.1. Information on toxicological effects

#### **Acute toxicity**

Harmful if swallowed.

Harmful in contact with skin.

Harmful if inhaled.

turpentine, oil

oral, LD50, Rat: 5760 mg/kg

Methanol

oral, LD50, Rat: 5630 mg/kg dermal, LD50, Rabbit: 15800 mg/kg

inhalative (vapours), LC50, Rat: 83.9 mg/l (4 h)

## skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

turpentine, oil Skin (4 h) Irritating to skin.

Methanol

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 114XXX008 PAPER VARNISH

 Print date
 08.06.2020
 Revision date 20.09.2016
 EN

 Version
 1.0
 Issue date 20.09.2016
 Page 6 / 8

Skin, Rabbit (4 h)

Irritant.

## Respiratory or skin sensitisation

May cause an allergic skin reaction.

turpentine, oil

Skin:

May cause sensitization by skin contact.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

## Specific target organ toxicity

Toxicological data are not available.

#### **Aspiration hazard**

Toxicological data are not available.

#### Practical experience/human evidence

Other observations:

## **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### Remark

There is no information available on the preparation itself .

## **SECTION 12: Ecological information**

## overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

## 12.1. Toxicity

turpentine, oil

Daphnia toxicity, EC50: 14.1 mg/l (48 h)

Methanol

Fish toxicity, LC50: > 100 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/l (48 h)

Algae toxicity, ErC50, Scenedesmus quadricauda: > 100 mg/l

## Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

turpentine, oil

Fish toxicity, LC50 (96 h)

Methanol

Fish toxicity, LC50: 24000 mg/l (96 h)

## 12.2. Persistence and degradability

Toxicological data are not available.

## 12.3. Bioaccumulative potential

Methano

Partition coefficient: n-octanol/water: < 4

## **Bioconcentration factor (BCF)**

Toxicological data are not available.

#### 12.4. Mobility in soil

Toxicological data are not available.

## 12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

Version

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article No.: 114XXX008
Print date 08.06.2020

PAPER VARNISH
Revision date 20 09 20

Revision date 20.09.2016 EN Issue date 20.09.2016 Page 7 / 8

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

#### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

## List of proposed waste codes/waste designations in accordance with EWC

080111\* waste paint and varnish containing organic solvents or

other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## **SECTION 14: Transport information**

14.1. UN number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint Sea transport (IMDG): PAINT Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) UMWELTGEFÄHRDEND

Marine pollutant p / turpentine

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

## **Further information**

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 643 VOC-value (in g/L) ASTM D 2369: 643

**National regulations** 

## **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

## Other regulations, restrictions and prohibition regulations

## 15.2. Chemical Safety Assessment

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article No.: 114XXX008 PAPER VARNISH
Print date 08.06.2020 Revision date 20.09.2016
Version 1.0 Issue date 20.09.2016

Chemical safety assessments for substances in this preparation were not carried out.

## 16. Other information

## Full text of classification in section 3:

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

Acute Tox. 4 / H332 Acute toxicity (inhalative) Harmful if inhaled.

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skin.

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.

Asp. Tox. 1 / H304 Aspiration hazard May be fatal if swallowed and enters airways.

Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation.

Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.
Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

Flam. Liq. 2 / H225 Flammable liquids Highly flammable liquid and vapour.

Acute Tox. 3 / H331 Acute toxicity (inhalative) Toxic if inhaled.

Acute Tox. 3 / H311 Acute toxicity (dermal) Toxic in contact with skin.

Acute Tox. 3 / H301 Acute toxicity (oral) Toxic if swallowed.

STOT SE 1 / H370 Specific target organ toxicity (single Causes damage to organs (or state all organs

exposure) affected, if known) (state route of exposure if it is conclusively proven that no other routes of

exposure cause the hazard).

ΕN

Page 8 / 8

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.