Article Print da Versio	ate 08.06.2	020 Revisio	ENTINE OIL THIN on date 11.04.201 late 11.04.2017		EN Page 1 / 7	
	SECTION 1: Ident	tification of the s	ubstance/mixtu	ure and of the	company/undertaking	
1.1.	product identifiers					
	Article No. (manufacturer/supplier): 114XXX016					
	Identification of the s	substance or mixtur	e TUF	RPENTINE OIL	THINNER	
1.2.	Relevant identified uses:					
	Artists supply and he Coatings and paints		ovors			
	Details of the supp	-				
	Supplier (manufact	-		stributor):		
	Canson Australia	uren/importen/uow		stributor).		
	6/26-30 Foundry Roa	ad		phone: 028825		
	Seven Hills NSW 21	47	Eme	ergency telepho	ne: 131126	
	Dept. responsible f	or information:				
	E-mail		sale	s.au@canson.c	com	
1.4.						
	SECTION 2: Haza	rds identificatio	n			
2.1.	Classification of th	e substance or mi	xture			
	Classification acco	ording to Regulation	on (EC) No 1272/2	2008 [CLP]		
	Flam. Liq. 3 / H226		able liquids		Flammable liquid and vapour.	
	Acute Tox. 4 / H302 Acute Tox. 4 / H312		oxicity (oral) oxicity (dermal)		Harmful if swallowed. Harmful in contact with skin.	
	Acute Tox. 4 / H332		oxicity (inhalative)		Harmful if inhaled.	
	Skin Irrit. 2 / H315		rosion/irritation		Causes skin irritation.	
	Eye Irrit. 2 / H319		eye damage/eye		Causes serious eye irritation.	
	Skin Sens. 1 / H317 Asp. Tox. 1 / H304		tory or skin sensit on hazard	isation	May cause an allergic skin reaction. May be fatal if swallowed and enters airways.	
	Aquatic Chronic 2 / F		ous to the aquatic	environment	Toxic to aquatic life with long lasting effects.	
	Label elements		·			
	The product is class	ified and labelled a	ccording to EC dir	ectives or corre	sponding national laws.	
	Labelling according		-			
	Hazard pictograms	- - .	·	<u> </u>		
			SL			
			12	Danger		
	Hazard statements					
	H226	Flammable liquid	l and vapour.			
	H302 + H312 + H332				led.	
	H304 H319		vallowed and ente	rs airways.		
	H315	Causes serious e Causes skin irrita				
	H317		ergic skin reactior	۱.		
	H411 Toxic to aquatic life with long lasting effects.					
	Precautionary statements					
	P101 P102	Keep out of the r		broduct containe	er or label at hand.	
	P103	Read label befor				
	P210	Keep away from	heat, hot surfaces	s, sparks, open f	flames and other ignition sources. No smoking.	
	P233	Keep container ti		+ (
	P261 P270		dust/fume/gas/mis or smoke when u			
	P270 P271		s or in a well-vent		л.	
	P272				l out of the workplace.	
	P273	Avoid release to				

P273 Avoid release to the environment.

Article No.: Print date Version	114XXX016 08.06.2020 1.1	TURPENTINE OIL THINNER Revision date 11.04.2017 Issue date 11.04.2017	EN Page 2 / 7		
P280	Wea	r protective gloves/protective clothing/e	eye protection/face protection.		
P301 + P31	0 IF S\	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P302 + P35	2 IF O				
P304 + P34	0 IF IN				
P305 + P35	1 + P338 IF IN	EYES: Rinse cautiously with water for	several minutes. Remove contact lenses, i	f present and	
	easy	to do. Continue rinsing.			
P331	Do N	OT induce vomiting.			
P332 + P31	3 If ski	n irritation occurs: Get medical advice/a	attention.		
P337 + P31	3 If eye	e irritation persists: Get medical advice	attention.		
P362 + P36	4 Take	off contaminated clothing and wash it	before reuse.		
P370 + P37	'8 In ca	se of fire: Use foam to extinguish.			
P405	Keep	locked up.			
P501	Disp	ose of contents/container in accordanc	e with local legislation.		
contains:					
	turpe	ntine, oil			
Supplement	tal Hazard info	rmation (EU)			

Supplemental Hazard information (EU)

not applicable

2.3. Other hazards

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

SECTION 3: Composition / information on ingredients

3.1. Substances

Description	Painting Medium for Oil-Colour
-------------	--------------------------------

Hazardous ingredients

EC No.	REACH No.	
CAS No.	Chemical name	Wt %
INDEX No.	classification:	Remark
232-350-7		
8006-64-2	turpentine, oil	50 - 100
650-002-00-6	Flam. Liq. 3 H226 / Acute Tox. 4 H332 / Acute Tox. 4 H312 / Acute Tox. 4	
	H302 / Asp. Tox. 1 H304 / Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin	
	Sens. 1 H317 / Aquatic Chronic 2 H411	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Article No.:	114XXX016	TURPENTINE OIL THINNER	
Print date	08.06.2020	Revision date 11.04.2017	EN
Version	1.1	Issue date 11.04.2017	Page 3 / 7

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Vapours form explosive mixtures with air.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Vapours form explosive mixtures with air.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Article No.:	114XXX016	TURPENTINE OIL THINNER	
Print date	08.06.2020	Revision date 11.04.2017	EN
Version	1.1	Issue date 11.04.2017	Page 4 / 7

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

turpentine, oil

INDEX No. 650-002-00-6 / EC No. 232-350-7 / CAS No. 8006-64-2 TWA: 566 mg/m3; 100 ppm STEL: 850 mg/m3; 150 ppm

Additional information

TWA : long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Appearance:	Liquid					
	Physical state	Liquid					
	Colour	refer to label					
	Odour	characteristic					
	Safety relevant basis data		Unit	Method	Remark		
	Flash point:	= 34	°C	DIN 53213			
	Ignition temperature in °C:	220	°C				
	Lower explosion limit	0,7	Vol-%				
	Upper explosion limit	6,1	Vol-%				
	Vapour pressure at 20 °C::	2,5					
	Density at 20 °C::	1,00	g/cm³				
	Water solubility (g/L)	insoluble					
	pH at 20 °C::	-					
	Viscosity at 20 °C:	< 50	mPa*s				
	Solvent separation test (%)	< 3	%				
	boiling point in °C at 101,3 kPa	150	°C				
2	Other information:						

9.2. Other information:

Article No.:	114XXX016	TURPENTINE OIL THINNER	
Print date	08.06.2020	Revision date 11.04.2017	EN
Version	1.1	Issue date 11.04.2017	Page 5 / 7

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. Vapours form explosive mixtures with air.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Harmful in contact with skin.

Harmful if inhaled.

turpentine, oil oral, LD50, Rat: 5760 mg/kg

skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

turpentine, oil Skin (4 h) Irritating to skin.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

turpentine, oil

Skin:

May cause sensitization by skin contact.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Article No.:	114XXX016	TURPENTINE OIL THINNER	
Print date	08.06.2020	Revision date 11.04.2017	EN
Version	1.1	Issue date 11.04.2017	Page 6 / 7

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

turpentine, oil

Daphnia toxicity, EC50: 14.1 mg/l (48 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

turpentine, oil

Fish toxicity, LC50 (96 h)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

140603* other solvents and solvent mixtures

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. Send to a collecting point for used paints.

SECTION 14: Transport information

14.1. UN number

	UN 1299
 14.2. UN proper shipping name Land transport (ADR/RID): Sea transport (IMDG): Air transport (ICAO-TI / IATA-DGR): 	Turpentine TURPENTINE Turpentine
14.3. Transport hazard class(es)	_
	3
14.4. Packing group	Ш
14.5. Environmental hazards	
Land transport (ADR/RID)	UMWELTGEFÄHRDEND
Marine pollutant	p / turpentine
14.6. Special precautions for user	

Article Print o Versio	date	114XXX016 08.06.2020 1.1	TURPENTINE OIL THINNER Revision date 11.04.2017 Issue date 11.04.2017	EN Page 7 / 7				
	case of an	Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8						
	Further inf	ormation						
	Land transport (ADR/RID) tunnel restriction code D/E							
	Sea transp	ort (IMDG)						
	EmS-No.		F-E, S-E					
14.7.	Transport	in bulk according	to Annex II of Marpol and the IBC C	ode				
	not applical	ble						
	SECTION	15: Regulatory	information					
15.1.	Safety, hea EU legislat		nental regulations/legislation specifi	c for the substance or mixture				
	VOC-value	n according to 19 (in g/L) ISO 11890 (in g/L) ASTM D 2	0-2: 860	ns of volatile organic compounds (VOC-guideline).				
	National re							
	Restrictions of occupation Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).							
	Other regu	lations, restrictio	ons and prohibition regulations					
15.2.		Safety Assessme	nt I safety assessment has not been carr	ed out.				
16.	Other info	ormation						
	Full text of Flam. Liq. 3 Acute Tox. Acute Tox. Acute Tox. Asp. Tox. 1 Eye Irrit. 2 Skin Irrit. 2	4 / H332 4 / H312 4 / H302 / H304 / H319	section 3: Flammable liquids Acute toxicity (inhalative) Acute toxicity (dermal) Acute toxicity (oral) Aspiration hazard Serious eye damage/eye irritation skin corrosion/irritation	Flammable liquid and vapour. Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.				

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1.It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.