# 29- Safety Data Sheet

# Aerosol Crystal Clear

# COMPANY AND PRODUCT IDENTIFICATION

Company Name ABN Address Emergency Tel: Tel / Fax: Email:	Aaron Laboratories Pty Ltd 060 004 856 848 21 Kitchen Road, Dandenong, VIC, 3175 (+614) 1817 9157 (+614) 0730 0286 (+613) 9706 7673 / (+613) 9706 7622 joseph@aaronlab.com.au
Product Name	Nuart Crystal Clear 400g
Other Names	Not relevant
Manufacturers Code Recommended use	S&S 005 Art and craft
Recommended use	
Poisons Information Cent	
AUSTRALIA NEW ZEALAND	13 11 26 0800 764 766 or 0800 POISON
	0800 704 700 01 0800 POISON
	HAZARD(S) IDENTIFICATION
Hazard Classification	This product is classified as hazardous under Australian WHS Regulations. This product is classified as a Dangerous Good by the Australian Dangerous Goods Code.
	Flammable Aerosols, Cat 1
	Skin corrosion/irritation, Cat 2
	Serious eye damage/eye irritation, Cat 2
	Carcinogenicity, Cat 2
Hazard Statement(s)	Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. H222 Extremely flammable aerosol
	H280 Contain gas under pressure; may explode if heated
	H315 Causes serious skin irritation
	H319 Causes serious eye irritation H351 Suspected of causing cancer
	11351 Suspected of Causing cancer
Signal	Danger
Hazard Symbol	
v	

Precautionary	P101 If medical advice is needed, have product container or label at
Statement(s)	hand.
~ /	P102 Keep out of reach of children.
	P103 Read label before use.
	P210 Keep away from heat/sparks/open flames/hot surfacesNo smoking.
	P211 Do not spray on an open flame or other ignition source.
	P251 Pressurized container: Do not pierce or burn, even after use.
	P260 Do not breathe dust/fumes/gas/mist/vapours/spray.
	P262 Do not get in eyes, on skin, or on clothing.
	P281 Use personal protective equipment as required.
	P271 Use only in a well-ventilated area.
	P312 Call a POISON CENTER/ doctor if you feel unwell.
	P305 IF IN EYES: wash out immediately with water.
	P302 IF ON SKIN: remove contaminated clothing and wash thoroughly.
	P301 + P331 IF SWALLOWED: rinse mouth with water. Do NOT induce vomiting.
	P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding $50^{\circ}C/122^{\circ}F$ .

For further health and safety information please refer to the full SDS.

Note: This product should not be used in any purpose or manner contrary to recommended use unless authorised.

#### **COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Name</b> Xylene Dichloromethane	<b>CAS Number</b> 1330-20-7 75-09-2	<b>Proportion</b> 10-30% 10-30%
Hydrocarbon propellant - Propane - Butane	74-98-6 106-97-8	30-60%
Other ingredients		to 100%

# FIRST AID MEASURES

For advice, contact a Poisons Information Centre 131126 or a doctor. Ensure medical personnel are aware of the identity and nature (hydrocarbon propelled aerosol) involved.

**Inhalation:** Remove victim to fresh air to prevent further exposure. Propane is an asphyxiant. If breathing difficulties are experienced, seek immediate medical care. Do not use direct mouth to mouth method of resuscitation, use alternative respiratory method.

Skin Contact: Remove contaminated clothing and shoes and wash well skin with warm soapyIssue Date: 30/11/19Page 2 of 6

water. If irritation persists, contact a doctor

**Eye Contact:** Flush out immediately with running water for at least 15 minutes. If symptoms persist, seek medical attention.

**Ingestion:** Due to high volatility of product, this is not likely to occur. If sprayed in mouth, rinse mouth with plenty of water. If swallowed, do NOT induce vomiting. Seek medical attention.

#### FIRE FIGHTING MEASURES

Beware- heat greater than 50 C / 122 °F may cause these extremely flammable, pressurised dispensers to rupture, and violently rocket in various directions. These rockets will release flammable and potentially toxic gasses, which will increase the risk of fire spreading. In extinguishing any fire beware of any residual unburnt gas that could reignite.

Suitable	Small fire: Use water spray/fog/foam, dry chemical or carbon dioxide (CO2).
Extinguishing	Large fire: Use water spray/fog/foam.
Media	
Hazards	Aerosols may rupture and rocket (become projectiles) when exposed to excessive heat. Released gases can form extremely flammable, invisible, odourless explosive mixtures with air. Released gases can be heavier than air and travel to source of ignition causing flashback. Hazardous concentrations can accumulate in a confined space (pits, low laying areas). Fire can produce irritating, poisonous and corrosive gases. High concentration of gas could cause dizziness or asphyxiation without warning
Precautions / PPE	For large quantities, consider initial evacuation for at least 100m in all directions. Fight fire from protected position or use unmanned hose holders or monitor nozzles.
	Use spark-proof tools and explosion-proof equipment. Wear SCBA and protective gloves. Structural firefighter's uniform provides limited protection. If large amounts are involved, wear SCBA and chemical splash suit. If impossible to safely extinguish fire, protect surroundings, withdraw from area and allow fire to burn.
Hazchem Code	If safe to do so, move undamaged aerosols from fire area but do not approach
(for Placarding	hot aerosols.
and transport	Cool aerosols with water before handling.
only)	2YE
	Class 2 flammable Gas

#### ACCIDENTAL RELEASE MEASURES

Spill is flammable (until LPG dissipates). Eliminate all sources of ignition
including static discharge. Wear protective gloves and safety glasses to
prevent contamination of skin and eyes.
Minor spills: Keep area well ventilated and wipe up.
Major spills:
Isolate spill or leak area for at least 8 m in all directions. Eliminate all sources
of ignition within at least 15 m.
Keep upwind and to higher ground (propellant gas is heavier than air and will

	seek low points, pay special attention to drains and pits- these will likely be explosive environments). Major fire:
	Consider initial evacuation for at least 100 m in all directions
Environmental	Notify police and fire brigade of the location, material, UN Number, quantity
Precautions	and emergency contact as well as condition and damage observed.
	Keep leaking containers away from drains, surface and ground water. Ensure
	leakage does not enter streams, sewers or drinking water supply.
Containment /	Eliminate all ignition sources, including static within at least 15 m. All
Clean up	equipment used when handling the product must be earthed.
Procedures	If water is available, spray leaking containers to reduce ignition hazard and
	disperse gas. Isolate area until gas has dispersed. Ventilate area. Avoid release
	to the environment. Do not empty into drains or natural waterways. Absorb
	spill with inert absorbent material (e.g. dry sand or earth) for disposal using
	an approved method or following local regulations.

## HANDLING AND STORAGE

Precautions for Safe Handling	Ensure spray nozzle is always directed away from user. Do not pierce or burn can after use. Extremely flammable- Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Do not breathe concentrated, vapour, mist or spray. Local exhaust ventilation may be necessary to minimise excessive vapour concentration (as long as they do not introduce risk of ignition), if levels are likely to be high or in a confined space.
Conditions for Safe Storage	Keep out of reach of children. Store in a well-ventilated area, away from damp or corrosive conditions. Protect from sunlight and do not expose to temperatures exceeding 50 °C / 122 °F. Store in accordance with Dangerous Goods Regulations and transport in accordance with the ADG Code for Dangerous Goods Class 2.1

### **EXPOSURE CONTROLS / PERSONAL PROTECTION**

National Exposure	There is no established TLV (Threshold Limit Value) for this product. Avoid exposure – obtain special instructions before use.
Standards	Butane - TWA (Time-Weighted Average) is 800ppm / 1900mg/m <sup>3</sup>
	Propane is an asphyxiant
<b>Biological Limit</b>	Not available.
Values	
Engineering	No smoking. No flames or sources of ignition. Local exhaust ventilation
Controls	may be necessary to minimise excessive vapour concentration, if levels are
	likely to be high or in a confined space.
Personal	Personal Protective Equipment is not required under normal conditions of
Protective	use., When handling bulk quantities, wear protective gloves and safety
Equipment (PPE)	glasses. Do not exceed exposure limits

### PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Aerosol, Fine clear spray
Odour	Solvent like
pH	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Boiling point	-42 to 0°C
(propellant)	
Solubility in Water	Immiscible
Specific Gravity	0.58 approx
(propellant)	
Flash Point (propellant)	-104 to -60°C
Flammable limits	1.5% to 9.6% in air (v/v)
(propellant)	
Ignition Temperature	494°C to 600°C
(propellant)	

#### STABILITY AND REACTIVITY

Chemical Stability Conditions to avoid	Stable under normal ambient conditions of storage and use. Avoid heat sources. Aerosol cans may explode/burst violently when subject to extremes of heat or pressure and may become projectiles. Heat, flames and sparks. Avoid static charge and discharge with high concentrations and in confined space. Avoid damp or corrective
	concentrations and in confined space. Avoid damp or corrosive conditions.
Incompatible Materials /	Can react violently with oxidising agents – chlorine, pool chlorine or
<b>Hazardous Reactions</b>	nitric acid.
Hazardous	Products may include oxides of carbon and nitrogen.
<b>Decomposition Products</b>	

#### TOXICOLOGICAL INFORMATION

Vapours may cause light-headedness, drowsiness and dizziness.
Ingestion: Unlikely due to high volatility of product, but maybe
harmful if swallowed.
Eyes: Liquid may cause damage. Vapour may cause irritation.
Skin: May cause cold burn. Irritating to skin.
Inhalation: Intentional misuse by deliberately concentrating and
inhaling contents can be harmful or fatal. May cause light-headedness,
dizziness and drowsiness. Excessive exposure may cause
unconsciousness or even death, due to asphyxiation.

#### ECOLOGICAL INFORMATION

The information provided is based on data available for the material and the components of the material.

Ecotoxicity / Persistence	Propellant will vaporise rapidly when released to atmosphere.
/ Degradability /	Propellant consists of hydrocarbons that photo chemically decompose
Mobility	under atmospheric conditions.

# DISPOSAL CONSIDERATIONS

Disposal of material must comply with local laws and regulations at time of disposal.

<b>Consumer Instructions</b>	Do not pierce or burn can. Containers can be disposed of in the normal
	household waste stream. Recycle empty can.
Bulk quantities	Dispose of according to Local, State and National regulations.

### TRANSPORT INFORMATION

Transport in accordance with the requirements of ADG Code.

UN Number	1950	
Proper Shipping Name	AEROSOLS	
(ADG 7, IMDG)		
Proper Shipping name	AEROSOLS, FLAMMABLE	
(IATA)		
<b>Emergency Procedure</b>	2D1	
Guide		
Class and subsidiary	2.1	
risk(s)		
Packaging Group	None allocated	
Hazchem Code	2YE	
Special Precautions for	Keep out of reach of children.	
Users	Spray in well-ventilated area.	
	Keep away from sources of ignition – No smoking.	
	Extremely flammable - Do not spray on a naked flame or any	
	incandescent material.	
	Always test spray on work sample before proceeding.	

# **REGULATORY INFORMATION**

Poisons Schedule	Not applicable
Additional information	Not applicable