

Aerosol Fixative

COMPANY AND PRODUCT IDENTIFICATION

Company Name Aaron Laboratories Pty Ltd

ABN 060 004 856 848

21 Kitchen Road, Dandenong, VIC, 3175 Address

(+614) 1817 9157 **Emergency Tel:**

 $(+614)\ 0730\ 0286$

(+613) 9706 7673 / (+613) 9706 7622 Tel / Fax:

joseph@aaronlab.com.au Email:

Product Name Nuart Fixative 350g

Other Names Not relevant **Manufacturers Code** S&S 006 Recommended use Art and craft

Poisons Information Centre

AUSTRALIA 13 11 26

NEW ZEALAND 0800 764 766 or 0800 POISON

HAZARD(S) IDENTIFICATION

Hazard Classification This product is classified as hazardous under Australian WHS

Regulations. This product is classified as a Dangerous Good by the

Australian Dangerous Goods Code.

Flammable Aerosols, Cat 1 Carcinogenicity, Cat 2

Hazard Statement(s) Intentional misuse by deliberately concentrating and inhaling contents

can be harmful or fatal.

H222 Extremely flammable aerosol.

H280 Contain gas under pressure; may explode if heated.

H351 Suspected of causing cancer

Signal Danger

Hazard Symbol





Precautionary P101 If medical advice is needed, have product container or label at **Issue Date: 30/11/19**

Page 1 of 6



Aerosol Fixative

Statement(s) hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. -No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fumes/gas/mist/vapours/spray.

P271 Use only in a well-ventilated area.

P312 Call a POISON CENTER/ doctor if you feel unwell.

P305 IF IN EYES: wash out immediately with water.

P302 IF ON SKIN: remove contaminated clothing and wash

thoroughly.

P301 + P331 IF SWALLOWED: rinse mouth with water. Do NOT

induce vomiting.

P410 + P412 Protect from sunlight. Do not expose to temperatures

exceeding 50°C/122°F.

For further health and safety information please refer to the full SDS.

Note: This product should not be used in any purpose or manner contrary to recommended use unless authorised.

COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name Dichloromethane	CAS Number 75-09-2	Proportion 10-30%
Hydrocarbon propellant - Propane - Butane	74-98-6 106-97-8	30-60%
Other ingredients		to 100%

FIRST AID MEASURES

For advice, contact a Poisons Information Centre 131126 or a doctor. Ensure medical personnel are aware of the identity and nature (hydrocarbon propelled aerosol) involved.

Inhalation: Remove victim to fresh air to prevent further exposure. Propane is an asphyxiant. If breathing difficulties are experienced, seek immediate medical care. Do not use direct mouth to mouth method of resuscitation, use alternative respiratory method.

Skin Contact: Remove contaminated clothing and shoes and wash well skin with warm soapy water. If irritation persists, contact a doctor

Eye Contact: Flush out immediately with running water for at least 15 minutes. If symptoms persist, seek medical attention.

Ingestion: Due to high volatility of product, this is not likely to occur. If sprayed in mouth, rinse mouth with plenty of water. If swallowed, do NOT induce vomiting. Seek medical attention.

Issue Date: 30/11/19 Page 2 of 6



Aerosol Fixative

FIRE FIGHTING MEASURES

Beware- heat greater than 50 C / 122 °F may cause these extremely flammable, pressurised dispensers to rupture, and violently rocket in various directions. These rockets will release flammable and potentially toxic gasses, which will increase the risk of fire spreading. In extinguishing any fire beware of any residual unburnt gas that could reignite.

Suitable

Extinguishing

Media Hazards Small fire: Use water spray/fog/foam, dry chemical or carbon dioxide (CO2).

Large fire: Use water spray/fog/foam.

Aerosols may rupture and rocket (become projectiles) when exposed to excessive heat. Released gases can form extremely flammable, invisible, odourless explosive mixtures with air. Released gases can be heavier than air

and travel to source of ignition causing flashback. Hazardous concentrations can accumulate in a confined space (pits, low laying areas). Fire can produce irritating, poisonous and corrosive gases. High concentration of gas could

cause dizziness or asphyxiation without warning

Precautions / PPE For large quantities, consider initial evacuation for at least 100m in all

directions.

Fight fire from protected position or use unmanned hose holders or monitor

nozzles.

Use spark-proof tools and explosion-proof equipment.

Wear SCBA and protective gloves. Structural firefighter's uniform provides limited protection. If large amounts are involved, wear SCBA and chemical

splash suit.

If impossible to safely extinguish fire, protect surroundings, withdraw from

area and allow fire to burn.

Hazchem Code (for Placarding

If safe to do so, move undamaged aerosols from fire area but do not approach

hot aerosols.

and transport
only)

Cool aerosols with water before handling.

2YE

Class 2 flammable Gas

ACCIDENTAL RELEASE MEASURES

Personal Precautions, PPE

Precautions, PPE and Emergency Procedures Spill is flammable (until LPG dissipates) . Eliminate all sources of ignition including static discharge. Wear protective gloves and safety glasses to

prevent contamination of skin and eyes.

Minor spills: Keep area well ventilated and wipe up.

Major spills:

Isolate spill or leak area for at least 8 m in all directions. Eliminate all sources

of ignition within at least 15 m.

Keep upwind and to higher ground (propellant gas is heavier than air and will seek low points, pay special attention to drains and pits- these will likely be explosive environments).

Major fire:

Consider initial evacuation for at least 100 m in all directions

Environmental Notify police and fire brigade of the location, material, UN Number, quantity

Issue Date: 30/11/19 Page 3 of 6



Aerosol Fixative

and emergency contact as well as condition and damage observed. **Precautions**

Keep leaking containers away from drains, surface and ground water. Ensure

leakage does not enter streams, sewers or drinking water supply.

Containment / Clean up **Procedures**

Eliminate all ignition sources, including static within at least 15 m. All

equipment used when handling the product must be earthed.

If water is available, spray leaking containers to reduce ignition hazard and disperse gas. Isolate area until gas has dispersed. Ventilate area. Avoid release to the environment. Do not empty into drains or natural waterways. Absorb spill with inert absorbent material (e.g. dry sand or earth) for disposal using

an approved method or following local regulations.

HANDLING AND STORAGE

Precautions for Safe Handling

Ensure spray nozzle is always directed away from user. Do not pierce or burn can after use. Extremely flammable- Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No

smoking. Do not breathe concentrated, vapour, mist or spray. Local exhaust ventilation may be necessary to minimise excessive vapour concentration (as long as they do not introduce risk of ignition), if levels are likely to be

high or in a confined space.

Conditions for Safe Storage

Keep out of reach of children. Store in a well-ventilated area, away from damp or corrosive conditions. Protect from sunlight and do not expose to temperatures exceeding 50 °C / 122 °F. Store in accordance with Dangerous Goods Regulations and transport in accordance with the ADG Code for

Dangerous Goods Class 2.1

EXPOSURE CONTROLS / PERSONAL PROTECTION

There is no established TLV (Threshold Limit Value) for this product. **National**

Avoid exposure – obtain special instructions before use. **Exposure**

Butane - TWA (Time-Weighted Average) is 800ppm / 1900mg/m³ **Standards**

Propane is an asphyxiant

Biological Limit

Values

Not available.

Engineering No smoking. No flames or sources of ignition. Local exhaust ventilation **Controls**

may be necessary to minimise excessive vapour concentration, if levels are

likely to be high or in a confined space.

Personal Personal Protective Equipment is not required under normal conditions of use., When handling bulk quantities, wear protective gloves and safety **Protective**

Equipment (PPE) glasses. Do not exceed exposure limits. .

PHYSICAL AND CHEMICAL PROPERTIES

Appearance Aerosol, Fine clear spray

Odour Solvent like Not available Hq Vapour Pressure Not available

Issue Date: 30/11/19 Page 4 of 6



Aerosol Fixative

Vapour Density
Boiling point
(propellant)

Not available -42 to 0°C

(propellant)

Solubility in Water Specific Gravity Immiscible 0.58 approx

(propellant)

Flash Point (propellant)

-104 to -60°C

Flammable limits

1.5% to 9.6% in air (v/v)

(propellant)

Ignition Temperature

(propellant)

494°C to 600°C

STABILITY AND REACTIVITY

Chemical Stability Stable under normal ambient conditions of storage and use. Avoid

heat sources. Aerosol cans may explode/burst violently when subject

Can react violently with oxidising agents – chlorine, pool chlorine or

to extremes of heat or pressure and may become projectiles.

Conditions to avoid Heat, flames and sparks. Avoid static charge and discharge with high

concentrations and in confined space. Avoid damp or corrosive

conditions.

Incompatible Materials /

Hazardous Reactions

nitric acid.

Hazardous

Products may include oxides of carbon and nitrogen.

Decomposition Products

TOXICOLOGICAL INFORMATION

Potential adverse health effects and symptoms associated with exposure to the material

Vapours may cause light-headedness, drowsiness and dizziness. **Ingestion**: Unlikely due to high volatility of product, but maybe harmful if swallowed.

Eyes: Liquid may cause damage. Vapour may cause irritation.

Skin: May cause cold burn. Irritating to skin.

Inhalation: Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. May cause light-headedness,

dizziness and drowsiness. Excessive exposure may cause unconsciousness or even death, due to asphyxiation.

ECOLOGICAL INFORMATION

The information provided is based on data available for the material and the components of the material.

Ecotoxicity / Persistence / Degradability /

Mobility

Propellant will vaporise rapidly when released to atmosphere.

Propellant consists of hydrocarbons that photo chemically decompose

under atmospheric conditions.

DISPOSAL CONSIDERATIONS

Issue Date: 30/11/19 Page 5 of 6



Aerosol Fixative

Disposal of material must comply with local laws and regulations at time of disposal.

Consumer Instructions Do not pierce or burn can. Containers can be disposed of in the normal

household waste stream. Recycle empty can.

Dispose of according to Local, State and National regulations. **Bulk quantities**

TRANSPORT INFORMATION

Transport in accordance with the requirements of ADG Code.

UN Number 1950

Proper Shipping Name AEROSOLS

(**ADG 7, IMDG**)

Proper Shipping name AEROSOLS, FLAMMABLE

(IATA)

Emergency Procedure 2D1

Guide

Class and subsidiary 2.1

risk(s)

Packaging Group None allocated

Hazchem Code 2YE

Special Precautions for

Keep out of reach of children. Users Spray in well-ventilated area.

Keep away from sources of ignition – No smoking.

Extremely flammable - Do not spray on a naked flame or any

incandescent material.

REGULATORY INFORMATION

Poisons Schedule Not applicable Additional information Not applicable

Issue Date: 30/11/19 Page 6 of 6