



## Zest-it® Clear Painting Medium

### Safety Data Sheet (CLP)





For occupational use not general public/consumer use

Jan.2017 sp375

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

<b>1.1 Product Identifier</b>	Zest-it® Clear Painting Medium	
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Blending medium for oil paint; oil pastels. Functional fluid. Facilitating fluid. Blending fluid.	
<b>Product Numbers</b>	ZCPM; 1000; 500; 250; 125; 50	Importer - S&S Wholesale Pty. Limited 18/10 Pioneer Avenue, Thornleigh NSW 2120 Tel: 1300 731 529 Fax: 1300 739 715
<b>1.3 Details of the supplier of the safety data sheet</b>	J and T Blackman Ltd. High Street, Barwell, Leicestershire. LE9 8DR Tel: 0116 2341001 Mob. 07885103576 email: msdssupport@zest-it.biz	Emergency Contact: S&S Wholesale Pty. Limited Tel: 1300 731 529 Fax: 1300 739 715
<b>1.4 Emergency telephone No</b>	National Poisons Information Service (UK) 0844 8920111 National Chemical Emergency Centre 08701906777 and +44(0)1270502891	

#### SECTION 2: HAZARDS IDENTIFICATION

<b>2.1 Classification of the substance or mixture</b>	
<b>Classification under CHIP; Directive 67/548/EEC or 1999/45/EC</b>	 Xn; Harmful: R65 may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking.
<b>Classification under CLP; Regulation (EC) No 1272/2008 Most important adverse effects.</b>	 Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. EUH066: Repeated exposure may cause skin dryness or cracking
<b>2.2 Label elements</b>	
<b>Label elements under CLP Hazard pictograms Signal word</b>	 Danger
<b>Hazard statements:</b>	H304 May be fatal if swallowed and enters airways. EUH066: Repeated exposure may cause skin dryness and cracking
<b>Precautionary statements:</b>	P301+331+315 If Swallowed: Do NOT induce vomiting: Get immediate medical advice/attention. P102: Keep out of reach of children: Wash hands after use.
<b>Label elements under CHIP Hazard symbols</b>	 Harmful
<b>Risk phrases</b>	R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking.
<b>Safety phrases</b>	S-62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label. S-02 Keep out of reach of children
<b>2.3 Other hazards</b>	The mixture contain no components considered to be either persistent, bioaccumulative, toxic (PBT) or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<b>3.2 Mixture</b>	Mixture of substances listed below with nonhazardous additions.	
Aliphatic Hydrocarbon CAS-No: 64742-47-8 Classification (EC 1272/2008) R65 R66	EC No: 265-149-8 Classification (67/548/EEC) H304 EUH066	70-95%
Orange Terpenes CAS-No: 8028-48-6 Classification (EC 1272/2008) R65 R10 R38	EC No: 232-433-8 Classification (67/548/EEC) H226 H304	1-15%
Linseed Oil CAS-No. 67746-08-1	Not a hazardous substance or mixture	20 - 40%
These materials are listed on the following inventories:	REACH, TSCA, DSL, ENCS, EINECS, AICS, ECL, ISHL, PICCS, KECl, ASIA-PAC and NZIoC	

#### SECTION 4: FIRST AID MEASURES

<b>4.1 Description of first aid measures</b>	
<b>General Info</b>	NEVER give anything by mouth to an unconscious person. If symptoms persist, always call Doctor
<b>Inhalation</b>	Remove from exposure, keep at rest; Supply fresh air; consult doctor in case of complaints.

## Zest-it® Clear Painting Medium

<b>Ingestion (swallowing)</b>	Immediately rinse mouth; drink plenty of water or milk. DO NOT induce vomiting. If vomiting occurs, keep head low; call for medical help immediately; transfer to hospital.
<b>Skin contact</b>	Promptly remove any soaked or contaminated clothing and shoes. Promptly wash skin with soap and water and rinse thoroughly. If skin irritation occurs consult a doctor.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for up to 15 minutes, holding the eyelid open. Remove contact lens. If irritation persists consult a doctor.
<b>4.2 Most important symptoms and effect, both acute and delayed.</b> No further relevant information available	
<b>4.3 Indication of any immediate medical attention and special treatment needed.</b> No further information	
<b>SECTION 5: FIRE FIGHTING MEASURES</b>	
<b>General information</b>	Insoluble in water. May product dense smoke. Do not breathe smoke. Use sand or soil.
<b>5.1 Extinguishing media</b>	Extinguish with foam, carbon dioxide (CO <sup>2</sup> ), dry powder, water fog, soil or sand. DO NOT use water jet as this will spread the fire.
<b>5.2 Special hazards arising from the substance or mixture</b>	May produce dense black smoke and toxic fumes. Carbon Oxides. Vapours are heavier than air; may ground travel to sources of ignition. Droplets can cause severe burns.
<b>5.3 Advice for Firefighters</b>	Wear self contained breathing apparatus for firefighting where necessary. Keep run-off water out of sewers and water courses. Dike for water control. Keep up wind to avoid fumes.
<b>SECTION 6: ACCIDENTAL RELEASE MEASURES</b>	
<b>6.1 Personal Precautions protective equipment and emergency procedures</b>	Spillage can be a slip hazard. Avoid contact with eyes and skin. Turn leaking containers leak-side up to prevent further escape. Keep unprotected persons away. Ensure adequate ventilation. There is a danger that rags and cloths used to clean up a spill, or even any absorbant material may spontaneously combust. Absorbants should be sprayed with water before disposal.
<b>6.2 Environmental Precautions</b>	Do not allow to enter drains, sewers or watercourses. Used or contaminated product should not be allowed to enter sewers or water courses. Contain the spillage using bunding.
<b>6.3 Method and material for containment and cleaning up</b>	Avoid sparks, flames. Ventilate. Absorb in vermiculite, dry sand or earth. Keep in suitable closed container for disposal. Dike to contain spread. Clean contaminated area with oil removing material.
<b>6.4 Reference to other sections</b>	
<b>SECTION 7: HANDLING AND STORAGE</b>	
<b>7.1 Precautions for safe handling</b>	Do not handle or use near open flames or sources of ignition. Prevent formation of aerosols or mists. Spillage can be a slip hazard. Use in well ventilated area.
<b>7.2 Precautions for safe storage, and any incompatibilities</b>	Store in original container in a cool dry well ventilated place. Keep away from sources of ignition, heat, spark or open flame. Keep container tightly closed
<b>7.3 Specific end use(s)</b>	Store in original container in a cool dry place tightly closed and away from children.
<b>SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION</b>	
<b>8.1 Control parameters</b>	Contains no substance with occupational exposure limit values
<b>8.2 Exposure controls</b>	
<b>General protective and hygienic measures</b>	Keep away from foodstuffs, beverages and feed. Wash and dry hands before breaks and at the end of work. Do not spray or form mists/aerosols.
<b>Respiratory protection</b>	No specific ventilation requirements noted. Avoid generating mists/aerosols.
<b>Eye Protection</b>	Wear approved tight fitting safety glasses where splashing is probable. Provide eye wash station.
<b>Hand/Skin Protection</b>	Wash and dry hands after use. Use appropriate hand lotion to prevent defatting and cracking of skin. For prolonged or repeated skin contact use suitable protective gloves. Nitrile rubber, PVA. Ensure gloves are manufactured/tested in accordance with BSEN 374.
<b>Body Protection</b>	Wear apron or protective clothing in case of splashes. Wash contaminated clothing before reuse. The type of protective equipment must be selected according to the concentration and amount of the substance at the specific workplace.
<b>SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES</b>	
<b>9.1 Information on the basic physical and chemical properties</b>	
<b>Boiling Point</b>	180-239 <sup>o</sup> C 760 mm Hg
<b>Density (SG)</b>	0.9 g/cm <sup>3</sup>
<b>Vapour Density</b>	4.5 @ 80 <sup>o</sup> C (Air=1)

## Zest-it® Clear Painting Medium

<b>Viscosity</b>	Slightly viscous
<b>Solubility in / Miscibility with water</b>	Insoluble in water
<b>Flash Point (°C)</b>	70 P/M Pensky-Martens
<b>Ignition Temperature</b>	180 <sup>0</sup> C (356 <sup>0</sup> F)
<b>Appearance</b>	Clear Liquid
<b>Odour</b>	Mild Hydrocarbon Solvent/Linseed-like
<b>Colour</b>	Clear slightly viscous orange liquid
<b>Danger of explosion</b>	No - Does not present an explosion hazard
<b>Melting point</b>	Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
<b>9.2 Other information</b>	No further relevant information available

### SECTION 10: STABILITY AND REACTIVITY

<b>10.1 Reactivity</b>	No data available
<b>10.2 Chemical stability</b>	Stabile under normal conditions. Avoid: heat, sparks, flames
<b>10.3 Hazardous reactions</b>	May be danger of spontaneous combustion of rags, cloths or inert absorbent soaked in oil mixture. Wash, soak with water or dry flat.
<b>10.4 Conditions to avoid</b>	Avoid exposing to heat and contact with strong oxidising/acid substances. Open flames and other sources of ignition. Very fine dispersions may possibly self ignite in contact with air
<b>10.5 Incompatible material</b>	Strong acids. Strong oxidizing substances.
<b>10.6 Hazardous decomposition products</b>	Toxic gases/vapours/fumes of Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Hydrocarbons and Oxides of Nitrogen (NO <sub>x</sub> ), dense black smoke.

### SECTION 11: TOXICOLOGICAL INFORMATION

<b>General Information</b>	Product has low toxicity. Only large volumes may have adverse impact on human health.
<b>11.1 Information on toxicological effects</b>	
Hazard of substance	Aspiration hazard.
<b>Symptom/routes of exposure</b>	
Ingestion	Pneumonia may be the result if vomited material containing solvent reaches the lungs.
Inhalation	If heated irritating vapours may be formed. Do not spray or cause mists.
Eye contact	Splashes may irritate.
Skin contact	May cause skin dryness and cracking.
Germ cell mutagenicity	This substance has no evidence of mutagenic properties.
Carcinogenicity	This substance has no evidence of carcinogenic properties.
Reproductive toxicity	This substance has no evidence of toxicity to reproduction or the unborn.
Medical considerations	Avoid vomiting and normal rinse of stomach because of risk of aspiration.

### SECTION 12: ECOLOGICAL INFORMATION

<b>12.1 Toxicity</b>	The product is not expected to be hazardous to the environment.
<b>12.2 Persistence and degradability</b>	Biodegradable
<b>12.3 Bioaccumulative potential</b>	Bioaccumulation is unlikely.
<b>12.4 Mobility in soil</b>	Readily absorbed into soil
<b>12.5 Results of PBT and vPvB assessment</b>	This substance is not identified as a PBT substance
<b>12.6 Other adverse effects</b>	Negligible ecotoxicity

### SECTION 13: DISPOSAL CONSIDERATIONS

<b>13.1 Waste treatment methods</b>	Disposal to licensed waste disposal site in accordance with Local Authority
-------------------------------------	---

### SECTION 14: TRANSPORTATION INFORMATION

<b>Transport class</b>	This product does not require a classification for transport.
<b>14.1 UN number</b>	No information required
<b>14.2 UN proper shipping name</b>	No information required

## Zest-it® Clear Painting Medium

<b>14.3 Transport hazard class(es)</b>	Not applicable. (IMDG; IATA; ADR; RID;)
<b>14.4 Packing group</b>	Not applicable.
<b>14.5 Environmental hazard</b>	Marine pollutant - no.
<b>14.6 Special precautions for user</b>	No information required
<b>14.7 Transport in bulk</b>	according to annex II of marpol73/78 and the IBC code
<b>SECTION 15: REGULATORY INFORMATION</b>	
<b>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	Chemicals (Hazard Information & Packaging for Supply) Regulations. UK Regulatory References Health and Safety at Work Act 1974. Guidance Notes Workplace Exposure Limits EH40. EU Legislation Regulation (EC) No 1907/2006 REACH Regulation (EC) No 1272/2008 CLP.
<b>15.2 Chemical Safety Assessment</b>	No chemical safety assessment has been carried out
<b>SECTION 16: OTHER INFORMATION</b>	
Revision Date (next rev 2023)	20.Nov.2018
Compilation date	11.Nov.15;20.Nov.2008; Jul.05
Sheet Reference	Zest-it® Clear Painting Medium
Product covered by this data sheet	All sizes of Zest-it® Clear Painting Medium
Phrases used in S 2 and 3	EUH066: Repeated exposure may cause skin dryness or cracking. H304: May be fatal if swallowed and enters airways. R-65 Harmful, may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking.
<ul style="list-style-type: none"> <li>• Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.</li> <li>• The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.</li> <li>• It is at all times the responsibility of the user to take all necessary measures to comply with safety precautions, legal requirements and local regulations.</li> <li>• The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.</li> <li>• This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.</li> </ul>	

Legal Disclaimer. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information contained in this document is furnished without warranty, guarantee or representation of any kind to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own particular use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. J and T Blackman Ltd t/a Zest-it shall not be held liable for any damage resulting from handling using or from contact with the above product.